

DELIVERY DIMENSIONS

Kerto® LVL products are manufactured to customer specifications. Kerto can be delivered within manufacturing limits of 1.8 m x 25 m (width x length) or wider 2.5 m x 20 m (width x length). Product thicknesses are from 21 mm to 75 mm. The standard thicknesses are available with 3 mm increments up to thickness of 33 mm and with 6 mm increments for thicker ones.

Other sizes within the maximum manufacturing size are available on request. Please contact your country's Metsä Wood sales organisation for further details.

KERTO-S STANDARD DIMENSIONS

TABLE 1. STANDARD SIZES OF KERTO-S BEAMS

Width (mm)	Height (mm)								
	200	225	260	300	360	400	450	500	600
27	•	•	-	-	-	-	-	-	-
33	•	•	•	-	-	-	-	-	-
39	•	•	•	•	•	-	-	-	-
45	•	•	•	•	•	-	-	-	-
51	•	•	•	•	•	•	-	-	-
57	•	•	•	•	•	•	•	-	-
63	•	•	•	•	•	•	•	•	-
75	•	•	•	•	•	•	•	•	•

Maximum product length is 25 m. Local transport restrictions may limit the length.



KERTO-Q STANDARD DIMENSIONS

TABLE 2. STANDARD SIZES OF KERTO-Q

Thickness (mm)													
	200	225	260	300	360	400	450	500	600	900	1200	1800	2400 / 2500
24	•	•	•	•	•	•	•	•	•	•	•	•	•
27	•	•	•	•	•	•	•	•	•	•	•	•	•
33	•	•	•	•	•	•	•	•	•	•	•	•	•
39	•	•	•	•	•	•	•	•	•	•	•	•	•
45	•	•	•	•	•	•	•	•	•	•	•	•	•
51	•	•	•	•	•	•	•	•	•	•	•	•	•
57	•	•	•	•	•	•	•	•	•	•	•	•	•
63	•	•	•	•	•	•	•	•	•	•	•	•	•
69	•	•	•	•	•	•	•	•	•	•	•	•	•
75	•	•	•	•	•	•	•	•	•	•	•	•	•

The product's maximum length for widths up to 1800 mm is 25 m and for widths over 1800 mm the maximum length is 20 m. Local transport restriction may limit the length.

KERTO-Qp STANDARD DIMENSIONS

Kerto-Qp standard beams

- 42 x 500 mm
- 51 x 620 mm
- 63 x 830 mm
- Maximum length 20 m.

KERTO-T DIMENSIONS

Typical dimensions of Kerto-T wall studs

TABLE 4. KERTO-T DIMENSIONS

Thickness (mm)	most commonly 39 mm or 45 mm
Width (mm)	< 200 mm
Length (mm)	< 8500 mm

Other sizes available (thicknesses 27 – 75 mm, maximum length 16 m).

